



Danhui LED Tri-proof Light

Product code	Watt	CCT/K	Lumens/lm	Lumens per watt	CRI	Beam Angle	Dimension	Dimmable
DH-LK12	36	2700-6500K	3600-5400	100-150	80	120°	1150x82x78mm	Optional
DH-LK15	48/60	2700-6500K	4800-9000	100-150	80	120°	1450x82x78mm	Optional
DH-LK18	70	2700-6500K	7000-10500	100-150	80	120°	1750x82x78mm	Optional
DH-LK12	36	2700-6500K	3600-5400	100-150	80	120°	1150x98x80mm	Optional
DH-LK15	48/60	2700-6500K	4800-9000	100-150	80	120°	1450x98x80mm	Optional
DH-LK18	70	2700-6500K	7000-10500	100-150	80	120°	1750x98x80mm	Optional

Features

- High efficiency 130lm/W, (optional 150lm/W)
- Slim design reduces weight by 20% for easier installation
- Compact package up to 15% more battens per container
- Only 6 clips- up to 40% quicker installation
- One DIP switch driver for mutiple sizes lamp
- Motion and daylight sensor, emergency options available
- Tough IK08 PC body with optional stainless steel clips
- Linkable
- Also available as SKD kit



Application

Packing lot/Workshop/Basement etc

