

Ultrathin Economical Commercial LED Downlight

- External driver with thermal cutout protection, Integrated die casting aluminum heat sink .
- Best heat dissipation, Powder coating surface, Quick connector, IC class, Supplied with flex and plug .
- High lumens output ,wide beam angle 110~120 degree.
- IP 20/IP 44 for front panel.
- 5 years warranty.



Product Code	Dimension (mm)	Cut-out (mm)	Depth (mm)	Watt (W)	Eq CFL Watt (w)	CCT (K)	Lumens (lm)	Lumens per watt (lm/w)	CRI (>=)	Dimmable
DH-DL10-OL	Φ113X60	90-98	56	10	18	3/4/5/6000	850	85	80	Optional
DH-DL15-OL	Φ143X65	120-135	80	15	26	3/4/5/6000	1350	90	80	Optional
DH-DL20-OL	Φ175X90	145-160	90	20	2*18	3/4/5/6000	2000	100	80	Optional
DH-DL25-OL	Φ230X120	192-210	120	25	2*18	3/4/5/6000	2500	100	80	Optional
DH-DL30-OL	Φ230X120	192-210	120	30	2*26	3/4/5/6000	3000	100	80	Optional

Die Casting Aluminum Downlight



UGR<19

3 Colors

